

Declaration of Performance



Red Deal Windows Ltd.

Unit 122 Tanner Business Centre, Greenfield

Oldham, OL3 7NH

13

DoP No: 1- 23/05/2013

Date of manufacture: See frame label

System 10/Rustique Internally Glazed Tilt & Turn Window, Intended for use in domestic or commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

Watertightness: NPD

Dangerous substances: None released under normal indoor use.

Resistance to wind load: NPD

Load-bearing capacity of safety devices: Pass, 350N when fitted (1)

Acoustic performance: NPD

Thermal transmittance: $\leq 1.6 \text{ W/m}^2\text{k}$ (2)

Radiation Properties: NPD

Air permeability: NPD

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

(1) Report No. 123/4567890/1 of 2 Issue 1 and 321/0987654/2 of 2 Issue 1, both dated 25.12.2012 for Safety & Security friction hinges with built in restrictor - BSI, Notified Test Body No. 0086

(2) Thermal Transmittance calculation approved by Buildcheck, Notified Test Body No. 1806. Ref Report No. CU 13238-3 Dated 18.06.2013

Name (Print)

Signed

Position

Date and Place of Issue