

Declaration of Performance



Red Deal Windows Ltd.

Unit 122 Tanner Business Centre, Greenfield

Oldham, OL3 7NH

13

DoP No: 1- 23/05/2013

Date of manufacture: See frame label

System 10/Rustique Open in/ Open out French doors Intended for use in domestic or commercial refurbishment or new building applications not on escape routes.

Annex ZA.1 of BS EN 14351-1:2006+A1:2010

Watertightness: NPD

Dangerous substances: None released under normal indoor use.

Impact resistance (glazed doors with injury risk only) : NPD

Resistance to wind load: NPD

Load-bearing capacity of safety devices: Not fitted

Ability to release: Not fitted

Height and Width (clear opening): NPD

Acoustic performance: NPD

Thermal transmittance: $\leq 1.6 \text{ W/m}^2\text{k}$ (1)

Radiation Properties: NPD

Air permeability: NPD

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A1:2010.

(1) Thermal Transmittance calculation approved by Buildcheck, Notified Test Body No. 1806. Ref Report No. CU 13238-6 Dated 20.06.2013

Name (Print)

Signed

Position

Date and Place of Issue